



ELECTRICAL THERMIC FLUID HEATER

It is designed on the principle of indirect heat transfer in shell & tube heat exchanger having forced circulation to give long life of electric heater & thermal oil.

Fully automatic operation with thyristor and PID controller.

High thermal efficiency 98%.

Suitable for outlet temp. Up to 300°C.

Completely factory assembled & compact design.

PLC & HMI option available for automation.



TECHNICAL DETAILS

Model No.	Unit	ATE-36	ATE-54	ATE-126	ATE-252	ATE-360	ATE-486	ATE-594	ATE-1400
Capacity	Kcal/Hr	30,000	45,000	1,00,000	2,00,000	3,00,000	4,00,000	5,00,000	12,00,000
Heater	Kw/ H	36	54	126	252	360	486	594	1404
Pump	HP	2	3	5	7.5	7.5	7.5	10	25

Higher capacity available on request.

SALIENT FEATURES



Fully Automatic



Maintenance Free



High Efficiency 98%



Smokeless so clean & safe



Skid Mounted Easy to install



Compact & Clean so it can be installed anywhere

CLIENTELE

EXPORTS



DOMESTIC



sales@ascentmes.com +91 88980 84020 www.ascentmes.com

Shop No. 2, 1st Floor, Nalanda Shopping Center, Station Road, Goregaon West, Mumbai - 400062, Maharashtra, India

